



NOTES:

1. PIVOT ROD 7/8" DIA, SLOPPY FIT THRU PIVOT TUBE OF SPEED SENSOR. MOUNT SPACERS TO PREVENT END-PLAY BEYOND APPROX 1/4"
2. LOCATE SPEED SENSOR TIRE ABOUT 15" FROM RETURN ROLLER, TOWARD TAIL PULLEY, IN CENTER OF BELT
3. WEIGHT OF SPEED SENSOR ASSEMBLY IS CORRECT FOR PROPER TRACTION **DO NOT** ADD MORE WEIGHT
4. SECURE CABLE TO AVOID ABRASION OR RESTRAINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES, TOLERANCES ARE:		CAD DRAWING, DO NOT MANUALLY UPDATE THIRD ANGLE PROJECTION		TEGWEIGH 1811 Buerkle Rd., St. Paul, MN 55110	
WELDMENTS .XX ± .06 ± 1.0 .XXX ± .032		ASSEMBLIES .XX ± .12 ± 1.0 .XXX ± .063		DATE 9/11/2008	TITLE: OUTLINE DIMENSIONS SPEED SENSOR, STANDARD MODEL SS12-01
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TECNETICS INDUSTRIES INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF TECNETICS INDUSTRIES INC. IS STRICTLY PROHIBITED.				APPROVED	
DO NOT SCALE FROM DRAWING		SIZE A	DRAWING NUMBER 21184300	REV	SCALE 1:12
				SHEET 1 OF 1	